

CLAIMS

1. Stapler (1) for stapling together a workpiece (15), primarily a sheaf of papers, with a staple (11), which stapler comprises a base part (2) and a
5 stapling unit (3) which, by means of connecting devices (4), are connected in such manner that they can be moved towards and away from each other in a reciprocating stapling movement (R), and which stapling unit incorporates a magazine (9) in which staples (11) are stored and a driver (14) which, during the stapling movement, drives a staple which is
10 formed into a shape consisting of a first and a second leg (40,41) with an intermediate crown (42) through an outlet opening (13) connected to the magazine, and in which the base part consists of a lower part (5) and an upper part (6), which is connected to the lower part in such manner that it can be moved towards and away from the lower part, and between which
15 parts is arranged a first elastic element (8) which, in an initial position, moves the upper and lower parts apart, the upper part being provided with a surface (16) on which the workpiece to be stapled is placed and in which surface is arranged an opening (31) through which the legs of the staple driven by the driver pass after the legs have been driven through the
20 workpiece, and to which upper part bending devices (21,22) arranged pivotably about individual pivot pins (25,26) are connected in the area under the opening, the upper part, in the initial position, being blocked from being moved in a downward direction towards the lower part by means of a blocking arrangement (21,22,25,26,44,45) when the driver drives the
25 staple legs through the workpiece, and which blocking device is disengaged by means of a releasing device (53,54,55,56) when the driver has driven the staple to a position in which the staple crown (42) is in contact with the upper surface (17) of the workpiece (15), whereupon the upper part and stapling unit are moved towards the lower part, causing the bending
30 devices, by interaction with the lower part, to be moved, by pivoting about their respective pivot pins, in a direction towards the upper part, whereupon the staple legs are moved by the bending devices against the underside (18) of the workpiece, C H A R A C T E R I S E D I N T H A T the blocking arrangement comprises the bending devices (21,22) which, in the
35 initial position, are in blocking contact with the lower part (5), preventing the upper part (6) from being moved in the direction of the lower part and

in that the releasing arrangement comprises releasing legs (53,54) arranged on the stapling unit (3), which interact with releasing devices (55,56) arranged on the bending devices to release the bending devices from the blocking position.

5

2. Stapler (1) in accordance with claim 1, C H A R A C T E R I S E D I N T H A T the bending devices (21, 22) are provided respectively with a first contact point (47,48) which, in the initial position, are in contact individually with the lower part (5) at respective second contact points (49,50), each of which points is located essentially directly below the pivot centre (51,52) of a respective bending device

3. Stapler (1) in accordance with any of the foregoing claims, C H A R A C T E R I S E D I N T H A T the bending devices (21,22) are moved to their initial position by an third elastic element (36).

4. Stapler (1) in accordance with any of the foregoing claims, C H A R A C T E R I S E D I N T H A T the bending devices (21,22) are prevented by latches (61) from being pivoted in a direction opposite to that in which the bending devices bend the staple legs.

25

30

35

SUMMARY

Stapler (1) which comprises a base part (2) and a stapling unit (3) which
 5 are connected together in such manner that they can be moved towards and
 away from each other in a reciprocating stapling movement (R), the
 stapling unit incorporates a magazine (9) in which staples (11) are stored
 and a driver (14) which, during the stapling movement, drives a staple
 which comprises a first and a second leg (40,41) with an intermediate
 10 crown (42) through an outlet opening (13) connected to the magazine, the
 base part consists of a lower part (5) and an upper part (6), which is
 connected to the lower part in such manner that it can be moved towards
 and away from the lower part, and between which parts is arranged a first
 elastic element (8) which, in an initial position , moves the upper and
 15 lower parts apart, the upper part being provided with a surface (16) on
 which a workpiece (15) to be stapled is placed and in which surface is
 arranged an opening (31) through which the legs of the staple is driven
 after that the legs have been driven through the workpiece, and to which
 upper part bending devices (21,22) arranged pivotably about individual
 20 pivot pins (25,26) are connected in the area under the opening, the upper
 part being blocked from being moved downward towards the lower part by
 means of a blocking arrangement (21,22,25,26,44,45) when the driver
 drives the staple legs through the workpiece, and which blocking device is
 disengaged by means of a releasing device (53,54,55,56) when the staple
 25 is driven to a position in which the staple crown (40) contacts the upper
 surface (17) of the workpiece, whereupon the upper part and stapling unit
 are moved towards the lower part, causing the bending devices, by
 interaction with the lower part, to be moved, by pivoting about their
 respective pivot pins, in a direction towards the upper part, whereupon the
 30 staple legs are moved by the bending devices against the underside (18) of
 the workpiece the blocking arrangement comprising the bending devices
 (21,22) which, in the initial position, are in blocking contact with the
 lower part (5), preventing the upper part (6) from being moved in the
 direction of the lower part.

35

Fig. 5